Ceramica Etc
beyond ceramics

TECHNICAL CHARACTERISTICS OF CALEIDO TILE COLLECTION 30.5 x 30.5 cm

Test	Applied Method	Wall
Flexural Strength	ISO 10545-1	39.23 N/mm^2
Abrasion Resistance	ISO 10545-7	N/A
Coefficient of Friction	ANSI A137.1	≥ 0.42 Wet
Thermal Shock Resistance	ANSI A137.2	Withstands 70 °C to 15 °C
Scratch Hardness	EN 101	7 Mohs
Acid Resistance	ISO 10545-13	Resistant, except to Hydrofluoric Acid
Stain Resistance	ISO 10545-13	Resistant
Alkali Resistance	ISO 10545-13	Resistant
Freeze Resistance	ISO 10545-12	Resistant
Squareness	ISO 10545-2	N/A
Crazing Resistance	ISO 10545-11	Resistant
Warpage	ISO 10545-2	N/A
Thickness	ISO 10545-2	N/A

	2x2	Hexa 1.75	2x6
Length	30.5 cm	32 cm	30.5 cm
Width	30.5 cm	31 cm	30.5 cm
Thickness	6.5 mm ± 1	6.5 mm ± 1	6.5 mm ± 1

Packing

Collection	Finish	Pieces per Box	m^2 per Box		Boxes per Pallet	Pallet Weight (kg)
Caleido 2x2 Mosaic	Matte & Glossy	11.00	1.02	16.95	60.00	1,017.00
Caleido 2x6 Mosaic	Matte & Glossy	11.00	1.02	17.10	60.00	1,026.00
Caleido 1.75 Hexagon Mosaic	Matte & Glossy	11.00	1.09	17.00	60.00	1,020.00

Notes
Suitable for shower floors in 2" x 2", 1.75" hexagon, and 2" x 6" formats.
For swimming pool applications, the use of epoxy grout is recommended to achieve better sealing and greater durability.
This product is manufactured using 100% recycled glass, making it an environmentally friendly and sustainable alternative.
Due to its composition, small particles from different types of recycled glass may be present.